

JPBasic

End-of-Life Information

Grundfos JPBasic water pumps must be disposed of according to local regulations by using a public or private waste collection service. If this is not possible, contact the nearest Grundfos company or service workshop.

Safety Risk

- Safety related to materials used
There is no risk for people during the disassembly process posed by the materials used for the product.
- Safety related for handling the product
There is no risk for people when handling the product.

Disassembly of the Product

Disassembly of the Product

- Polypropylene (PP)
- Iron
- Copper
- Aluminium

and can therefore be recycled to a large extent – depending on the national possibilities for recycling.

The pump is assembled by using screws and bolts and can be disassembled with standard tools.

Designation	Name	Material	Special Disassembly Consideration
1	Pump body	Polypropylene (PP)	
2	Tube	Polypropylene (PP)	
3	Impeller	Polypropylene (PP)	
4	Chamber	Polypropylene (PP)	
5	Flange	Iron	
6	Terminal box cover	Polypropylene (PP)	
7	Capacitor	Electronic scrap	
8	Terminal box	Polypropylene (PP)	
9	Bearing	Iron	
10	Rotor with shaft	Iron, aluminium, copper	
11	Stator housing	Iron, copper	
12	Housing	Iron	
13	Fan	Polypropylene (PP)	
14	Fan cover	Polypropylene (PP)	

Additional materials:

Screws, gaskets, cable etc.: Various materials less than 5% of weight.

