Multilift MSS

End-of-Life Information

Grundfos Multilift MSS lifting stations must be disposed of according to local regulations by using a public or private waste collection service. If this is not possible, contact the nearest Grundfos company or service workshop.

Safety Risk

- Safety related to materials used
 - There is no risk for people during the disassembly process posed by the materials used for the product.
- Safety related for handling the product
 - Caution is required when accessing the inside of the tank as it may be toxic caused by the waste water. Care should be taken when handling due to the weight.
 - The oil chamber of the pump contains 60 ml non-toxic oil (Shell Ondina 15).

Disassembly of the Product

The main materials of the components are:

- Iron
- Stainless steel
- Aluminium
- Copper
- Polyethylene (PE)
- ABS (Acrylonitrile butadiene styrene)
- Polypropylene (PP)
- Electronic scrap
- Rubber materials (NBR)

and can therefore be recycled to a large extend - depending on the national possibilities for recycling.

Pump and none-return valve can be removed from the tank with standard tools.

None-return valve and controller box are assembled using screws and bolts and can be disassembled with standard tools.

The pump cannot be disassembled with standard tools as the covers and housing of the motor unit are welded. A saw might be of help here.

Designation	Name	Material	Special Disassembly Consideration
1	Collecting tank	PE (Polyethylene)	Caution: The inside of the tank may be toxic and contaminated because of the waste water
2	None-return valve	Cast iron	
3	Flange	PP (Polypropylene)	
4	Ring	PP (Polypropylene)	
5	Supporting pipe	PP (Polypropylene)	
6	Pressure tube	PP (Polypropylene)	
7	Motor unit	Stainless steel, copper and	The oil chamber of the pump contains 60 ml non-toxic oil

		aluminium	(Shell Ondina 15)
8	Impeller	Stainless steel	
9	Display board	Electronics	
10		ABS (Acrylonitrile butadiene styrene)	
11		Electronics	
Additional materials:		Screws, gaskets etc.: Various materials (steel, NBR) less than 5% of weight. The pump contains 60 ml non-toxic oil, Shell Ondina 15	







